

Building with conscience.

StoLit[®] Lotusan[®] Super-hydrophobic Exterior Textured Finish with Lotus-Effect[®] Technology

Facades



Stolit® Lotusan® superhydrophobic textured finish with Lotus-Effect® Technology keeps buildings' facades clean and attractive while saving money on maintenance and recoating.

StoLit Lotusan

Modeled on nature and the self-cleaning properties of the Lotus Leaf


Through biomimicry research and development, Stolit Lotusan exterior textured finish possesses a highly water-replellent surface similar to that of the lotus leaf. Dirt simply runs off with the water that falls on the facade with our Lotus-Effect Technology. The facade remains dry and attractive, while lowering maintenance costs by extending cleaning and recoat cycles.



Over time, standard exterior finishes pick up and hold dirt causing a prematurely aged appearance.


Exterior walls finished with StoLit Lotusan are cleaned as water immediately forms droplets and flows off, taking dirt particles on the surface with it.

Features	Benefits
Super-hydrophobic	 Extremely water repellent Outstanding resistance to soiling issues Improved resistance to mold, mildew and algae
Vapor Permeable	Allows substrate to breathe naturally, resists blisters caused by trapped water vapor
UV Resistant	Excellent color retention



Standard finish facades over time are visibly soiled. On weather exposed sides in particular, microorganisms find an ideal environment for colonization in the form of adequate moisture and nutrients from dirt deposits.

How Stolit Lotusan Works



Stolit Lotusan finish has a super hydrophobic surface that reduces the contact area for dirt and water. Droplits form and roll off, taking loose particles of dirt along with them. Water absorption is reduced by as much as 50% when compared to ordinary acrylic finishes, even after extended weather exposure.

Sto Americas

Sto Corp. 3800 Camp Creek Pkwy Building 1400, Suite 120 Atlanta, GA 30331 USA

Phone 1-800-221-2397 www.stocorp.com

ATTENTION

Sto products are intended for use by qualified professional contractors, not consumers, as a component of a larger construction assembly as specified by a qualified design professional, general contractor or builder. They should be installed in accordance with those specifications and Sto's instructions. Sto Corp. disclaims all, and assumes no, liability for on-site inspections, for its products applied improperly, or by unqualified persons or entities, or as part of an improperly designed or constructed building, for the nonperformance of adjacent building components or assembly or building may result in serious damage to this product, and to the structure of the building or its components. STO CORP. DISCLAIMS ALL WARRANTIES EXPRESSED OR IMPLIED EXCEPT FOR EXPLICIT LIMITED WRITTEN WARRANTIES ISSUED TO AND ACCEPTED BY BUILDING OWNERS IN ACCORDANCE WITH STO'S WARRANTY PROGRAMS WHICH ARE SUBJECT TO CHANGE FROM TIME TO TIME. For the fullest, most current information on proper application, clean-up, mixing and other specifications and warranties, cautions and disclaimers, please refer to the Sto Corp. website, www.stocorp.com.