






Stolit® Milano

An easy-to-apply, ultra-smooth exterior or interior decorative and protective wall finish

Stolit® Milano is a very fine, extremely workable finish for interior or exterior wall surfaces that yields more coverage than comparable products on the market. In just two to three coats, this versatile finish can achieve multiple decorative looks, from a fine grit texture to the industrial feel of ultra-smooth metal panels. Highly breathable and mildew resistant, Stolit® Milano can also be top coated to provide additional abrasion protection.

Traditional Fine Smooth Texture vs. Stolit® Milano Ultra-Smooth Finish



Stolit® Milano is an extremely versatile finish.







Color samples are for representation only. To confirm color choices, request a sample from your Sto representative.

Sto Corp.

S869A 07/16

3800 Camp Creek Parkway Building 1400, Suite 120 Atlanta, GA 30331

Phone: 404-346-3666
Toll Free: 1-800-221-2397
Fax: 404-346-3119





www.stocorp.com

Stolit® Milano Benefits:

Exceptional Design Versatility

- By varying application technique and coating combination, many looks can be achieved, including that of Venetian plaster, metal, and even concrete
- Suitable for both interior and exterior wall applications
- Integral color of finish results in a longer lasting, more uniform look
- Can be tinted in a range of colors from the Sto Color System

A More Cost-Effective, Time Efficient Application

- Easy 2-coat process to achieve an ultra-smooth exterior finish
- Requires no specialized application technique
- Provides more coverage than other 'smooth' finishes
- Low maintenance due to product's moisture resistance and vapor permeability
- Can be top coated for enhanced abrasion resistance

Safe for Applicators, Gentle on the Planet

- Ready-mixed product requiring no additives minimizes waste and potential errors
- Better workability results in reduced worker fatigue
- Water based, low VOC

Easy 5-Step Application for a Beautiful, Ultra-Smooth Finish.



1. Scrape or stone the base coat to remove trowel lines and other surface imperfections and remove surface dust.



2. Apply "Sto Primer Smooth" uniformly by spray or roller and allow to dry.



Apply a uniform coat of Stolit Milano by trowel and allow to dry.



 After the product has dried, sand any trowel lines or imperfections with 100-150 grit sand paper and remove surface dust.



 Apply second uniform coat of Stolit® Milano by trowel and allow to dry.

Contact your Sto Sales Representative for more information. Please visit us at **www.stocorp.com** or call us toll-free at **800-221-2397**.

ATTENTION

Sto products are intended for use by qualified professional contractors, not consumers, as a component of a larger construction assembly as specified by a qualified design professional, general contractor or builder. They should be installed in accordance with those specifications and Sto's instructions. Sto Corp. disclaims all, and assumes no, liability for on-site inspections, for its products applied improperly, or by unqualified persons or entities, or as part of an improperly designed or constructed building, for the nonperformance of adjacent building components or assemblies, or for other construction activities beyond Sto's control. Improper use of Sto products or use as part of an improperly designed or constructed larger assembly or building may result in serious damage to this product, and to the structure of the building or its components. STO CORP. DISCLAIMS ALL WARRANTIES EXPRESSED OR IMPLIED EXCEPT FOR EXPLICIT LIMITED WRITTEN WARRANTIES ISSUESD TO AND ACCEPTED BY BUILDING OWNERS IN ACCORDANCE WITH STO'S WARRANTY PROGRAMS WHICH ARE SUBJECT TO CHANGE FROM TIME TO TIME. For the fullest, most current information or proper application, clean-up and mixing and other specifications and warranties, cautions and disclaimers, please refer to the Sto. Corp. website, www.stocorp.com.